

Low Maintenance Tubular Lead Acid Battery

Model	Module Voltage	Nominal Capacity (Ah) at C ₁₀	Monobloc / Module Dimensions & Weight				Initial Charging Current (Amps)
			Length (+/- 10 mm)	Length (+/- 10 mm)	Length (+/- 10 mm)	Weight (Approx Kgs)	
2 Volt Cells							
TS 100P	2	100	131	166	430	12.7	5.0
TS 120P	2	120	131	166	430	13.8	6.0
TS 150P	2	150	131	166	430	13.8	7.5
TS 200P	2	200	198	162	425	20.0	10.0
TS 250P	2	250	198	162	425	21.2	12.5
TS 300P	2	300	249	169	429	27.4	15.0
TS 350P	2	350	366	171	526	40.9	17.5
TS 400P	2	400	366	171	526	42.4	20.0
TS 450P	2	450	366	171	526	43.7	22.5
TS 500P	2	500	366	171	526	45.4	25.0
TS 550P	2	550	366	171	526	46.9	27.5
TS 600P	2	600	366	171	526	48.2	30.0
TS 650P	2	650	400	192	530	57.1	32.5
TS 700P	2	700	400	192	530	60.2	35.0
TS 750P	2	750	400	192	530	61.9	37.5
TS 800P	2	800	400	192	530	63.3	40.0
TS 850P	2	850	418	170	688	75.0	42.5
TS 900P	2	900	418	170	688	77.0	45.0
TS 950P	2	950	418	170	688	79.9	47.5
TS 1000P	2	1000	418	170	688	82.4	50.0
6 Volt Monoblocs							
6TS 60 P	6	60	450	180	380	12.8	3.0
6TS 90 P	6	90	450	180	380	16.1	4.5
6TS 120 P	6	120	450	180	380	20.1	6.0
6TS 150 P	6	150	450	180	380	23.4	7.5
6TS 180 P	6	180	450	180	380	26.9	9.0
12 Volt Monoblocs							
6SB20PPT	12	20	260	173	235	9.0	2.0
6SB30PPT	12	30	260	173	235	12.0	3.0
6SB40PPT	12	40	260	173	235	13.0	4.0
6SB50PPT	12	50	410	174	245	16.0	5.0
6SB60PPT	12	60	410	174	245	20.0	6.0
6SB66PPT	12	66	410	174	245	20.3	6.6
6SB75PPT	12	75	410	174	245	21.5	7.5
6SB80PPT	12	80	513	212	248	23.5	8.0
6SB100PPT	12	100	513	212	248	28.0	10.0
6SB120PPT	12	120	518	275	250	35.0	12.0
6SB130PPT	12	130	518	275	250	37.0	13.0
6SB150PPT	12	150	518	275	250	42.0	15.0
XLTT 160	12	160	503	190	415	43.5	16.0
XLTT 180	12	180	503	190	415	48.5	18.0
XLTT 200	12	200	503	190	415	56.0	20.0

8 Volt Monoblocs - For Diesel Locomotive Cranking							
8V 290 Ah Hard Rubber	8	290	708	220	452	127	29.0
8V 450 Ah Hard Rubber	8	450	708	220	452	140	45.0
8V 450 Ah FRP Tray	8	450	710	224	460	140	45.0